



8x6 LOG PROFILES



D-PROFILE

DOUBLE
ROUND

A. CORNER OPTIONS

1. All 8x6 profiles are available with the following corner options.
 - a. Mortise & Tenon
 - b. Trim

B. LOG SIDING SKIRT BOARD

1. The following corner options receive (3) rows of log siding skirt board.
 - a. Mortise & Tenon
 - b. Trim

Note: Siding skirt board not supplied below porches or decks.


C. ALUMINUM SKIRT FLASHING

1. The following corner options receive aluminum skirt flashing in lieu of log siding.
 - a. Dovetail
 - b. Saddlenotch

Note: Aluminum skirt flashing is provided to assist with weatherization and should be covered with an exterior finish such as stone.

D. LOG STACK HEIGHT: (A) = 5 1/4"

E. LOG WIDTH: (B) = 7 3/8"



F. EXTERIOR WINDOW TRIM: 1 3/4" x 3 1/2"

G. PORCH

1. The 6x8 header is typically located in the 18th course
2. A porch roof typically has a 4/12 pitch.

H. LOFT FLOOR

1. 6x8 loft joists are typically located in the 19th log course:
2. Dimension from the top of subfloor to bottom of 6x8 loft joist = 7'-6 1/2"

3. Dimension from the top of subfloor to bottom of loft floor = 8'-1 3/4"
4. Dimension from the top of subfloor to top of loft floor = 8'-3 1/4"

I. TYPICAL COURSE TO SQUARE (*Stack heights noted allow for 1/2" notch removed from the 1st log course*).

1. Pre-fab truss roof systems are typically 19 courses to square (8'-3 1/4" stack height).
2. 2x12 rafter roof systems are typically 22 courses to square (9'-7" stack height).
3. Beam & purlin roof systems are typically 22 courses to square (9'-7" stack height).
4. 6x8 rafter roof systems are typically 22 courses to square (9'-7" stack height).
5. Round rafter roof systems are typically 22 courses to square (9'-7" stack height).
6. Dormers are typically 38 courses to square (16'-7" stack height).
7. Full two stories are typically 38 courses to square (16'-7" stack height).

